

CALCASOL

DEGRADATION BIOLOGIQUE INHERENTE (OECD 302 B):

Détermination de la dégradation biologique de substances organiques solubles dans l'eau dans un test statique (Test Zahn-Wellens / EMPA)

1. Informations générales

Institut de contrôle: BMG Engineering AG, Ifangstr. 11, CH-8952 Schlieren
Responsable du contrôle: Dr. D. Oggier
Echantillon d'analyse: CALCASOL
Numéro d'échantillon BMG: M1107-05614-01
Numéro de rapport BMG: A11-01291/c
Donneur d'ordre: M. O. Menegalli
Menegalli SA, rte du bois-genoud 1, CH-1023 Crissier
Date du mandat: 27 juillet 2011
Durée du test: 9.8.11 – 6.9.11 (28 jours)
Méthode de test: OECD 302 B, adopted July 17, 1992: "Inherent Biodegradability: Zahn-Wellens / EMPA Test".
Instructions standards: BMG-1018

Le test est effectué selon les directives ISO/IEC 17025.

Les données primaires et les copies du rapport de contrôle sont conservées dans les archives de BMG Engineering AG à Schlieren pendant 5 ans.

2. Conditions de test

Concentration: 796 mg/l (50.8 mg/l comme DOC)
Substance de référence: 50.2 mg/l diéthylène glycol (comme DOC)
Température: 22.5 ± 0.5° C
Matière sèche de la boue: 0.2 g/l
Inoculum: Boue active provenant de l'étape biologique de la centrale d'épuration de Werdhölzli (Zurich), non adaptée: 8.8.2011, 15.00.
Procédure d'analyse: Détermination DOC (limite de décèlement: 0.05 mg/l); Shimadzu TOC-5000, Shimadzu TOC-5050 ou Analytik Jena multi N/C 3100. Détermination du CO₂ libéré en % ThCO₂ (Minéralisation).

BMG ENGINEERING AG

3. Résultat de test

Dans les conditions de la procédure d'analyse et sur la base de la détermination DOC, le produit CALCASOL présente une élimination de **99%** après **14** resp. **28 jours** de test. Une élimination presque complète de l'échantillon d'analyse après 28 jours et à un **degré de minéralisation de 95%** ThCO₂ a pu être constatée sans période d'adaptation significative.

Les résultats montrent que, dans les conditions de la procédure d'analyse (OECD 302 B), CALCASOL présente une élimination de plus de 70% ("**ultimately biodegradable**").

Puisque une élimination de plus de 90% et un degré de minéralisation de plus de 70% à été constatée, CALCASOL peut être qualifié de **biologiquement bien dégradable**.

La substance de référence, diéthylène glycol, présente une élimination de 99% après 14 resp. 28 jours de test. Une minéralisation à un degré de 90% ThCO₂ après 28 jours a pu être constatée. Une élimination de plus de 70% après 14 jours démontre le choix approprié de l'inoculum et des conditions de test.

Le rapport intégral ainsi que les données primaires peuvent être examinés sur demande auprès du donneur d'ordre ou de l'institut de contrôle sous le numéro de rapport A11-01291/c.

14 septembre 2011



Dr. D. Oggier
Chef Adjointe Écotoxicologie

Des indications sur les spécifications de test (valeur limite de détermination, incertitudes des mesures) peuvent être obtenues sur demande. Les résultats de test indiqués se rapportent exclusivement à l'échantillon cité ci-dessus. Des extraits du rapport ne peuvent être reproduits sans l'accord écrit du laboratoire de contrôle.

CALCASOL

Inherent Biodegradability - Evaluation of the Aerobic
Biodegradability in an Aqueous Medium:

OECD 302 B: ZAHN-WELLENS / EMPA TEST

Report

BMG study no. A11-01291/c

September 2011

Page 1 of 14



Labors: Analytik, Ökotoxikologie,
Verfahrenstechnik

BMG ENGINEERING AG

Labors:
Ifangstrasse 11
CH-8952 Schlieren/Zürich

Tel. 044 732 92 92 • Fax 044 732 92 21
labors@bmgeng.ch
www.bmgeng.ch



S SCHWEIZERISCHER PRÜFSTELLENDIENST
T SERVICE SUISSE D'ESSAI
S SERVIZIO DI PROVA IN SVIZZERA
S SWISS TESTING SERVICE STS-No. 166

Contents

1	Preface	4
1.1	General.....	4
1.2	Responsibilities.....	4
1.3	Schedule.....	4
1.4	Archiving.....	4
1.5	Test Guidelines.....	4
1.6	Signature	5
1.7	Quality assurance statement.....	5
2	Summary	6
3	Purpose	6
4	Materials and methods.....	7
4.1	Test system and test conditions.....	7
4.2	Test substance	7
4.3	Reference substance.....	7
4.4	Test concentrations	8
4.5	Test procedure	8
4.6	Chemical analyses.....	8
5	Evaluation of the test results	9
5.1	Definitions.....	9
5.2	Calculation of the percentage biodegradation	10
5.3	Validity criteria	10
6	Data compilation	10
7	Results and discussion	11
7.1	Determination of biodegradation / elimination	11
7.2	Remarks and alterations of the standard procedure.....	11
7.3	Validity of the test	11

Tables

Table 1	Composition of the mineral salt medium	9
Table 2	DOC concentrations of test suspension, inoculum blank and procedure control and calculation of degradation data.....	12

Table 3 IC concentrations, calculated from the concentrations in the gas absorption bottles, of test suspension, inoculum blank and procedure control and corresponding degradation data..... 14

Figures

Figure 1 Degradation curve for CALCASOL. 13

1 Preface

1.1 General

Title	CALCASOL Inherent Biodegradability - Evaluation of the Aerobic Biodegradability in an Aqueous Medium: OECD 302 B: ZAHN-WELLENS / EMPA TEST
Sponsor	Menegalli SA rte du bois-genoud 1 CH-1023 Crissier
Study Monitor	Mr. Orlando Menegalli
Test Facility	BMG Engineering Ltd. Ifangstrasse 11 CH-8952 Schlieren

1.2 Responsibilities

Study Director	Dr. Daniela Oggier
----------------	--------------------

1.3 Schedule

Experimental starting date	9 August 2011
Experimental completion date	6 September 2011

1.4 Archiving

Raw data and a copy of the final report are stored in the archives of BMG Engineering Ltd. in Schlieren for 5 years.

1.5 Test Guidelines

The study procedures described in this study plan meet the requirements of the following test guidelines:

- Organisation for Economic Cooperation and Development. OECD Guidelines for the Testing of Chemicals - Inherent Biodegradability: Zahn-Wellens / EMPA Test, TG 302 B, adopted 17th July 1992.
- Commission Regulation (EC) No 440/2008 of 30 May 2008 laying down test methods pursuant to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), C.9. Zahn-Wellens Test. (O.J. L 142 of 31.5.2008).
- The test procedure was conducted as described in detail in BMG's standard operating procedure (Standardarbeitsanweisung BMG-1018).

1.6 Signature

BMG Engineering Ltd.
Ifangstrasse 11
CH-8952 Schlieren

BMG study no.	A11-01291/c
Test substance	CALCASOL
Title	CALCASOL Inherent Biodegradability - Evaluation of the Aerobic Biodegradability in an Aqueous Medium: OECD 302 B: ZAHN-WELLENS / EMPA TEST

Study Director: Dr. Daniela Oggier



Date: 14 September 2011

1.7 Quality assurance statement

It is certified that the test for inherent biodegradability of CALCASOL was carried out under the study director's supervision using the guidelines and standard operating procedures described in this report and that this report forms a true and accurate record of the procedures performed and of the results obtained.

The study was conducted in accordance with ISO/IEC 17025

Specifications about accuracy and precision of measurement methods will be given on request. All test results relate only to the afore-mentioned test substance. This report shall not be reproduced or utilized in the form of extracts by any means, electronic or mechanical, including photocopying and microfilm, except in full without the written approval of the testing laboratory.

2 Summary

The biodegradability of CALCASOL exposed to activated sludge of a municipal sewage treatment plant was investigated under aerobic static conditions.

Based on the data of the individual DOC determinations CALCASOL reached a biodegradation of 99% after 28 days.

The main degradation process occurred during the first 7 days, when more than 95% of the initial DOC was removed. Maximum biodegradation was attained after 10 days of incubation. No significant adaptation period (lag phase) was observed.

Significant elimination (27%) of the test substance due to adsorption to the activated sludge, on the glass surface or other physico-chemical processes was found as determined by means of DOC measurements 3 h after the start of the test.

The positive control, diethylene glycol, showed 99% biodegradation after 14 days of incubation thus confirming suitability of inoculum and test conditions. The test was considered valid, since the degradation of the reference compound reached more than 70% within 14 days of incubation.

The biodegradation of CALCASOL based on CO₂ evolution and calculated as % ThCO₂ reached 95% after 28 days of incubation, showing that the main part of the organic carbon of the test material was transformed into CO₂. The extent of mineralization of the procedure control with diethylene glycol was within the same range showing a value of 90% based on ThCO₂.

Based on these results CALCASOL can be termed as ultimately biodegradable under the conditions of the OECD guideline no. 302, since more than 70% degradation was attained after 28 days of contact time.

3 Purpose

The objective of this study was to determine the biodegradability of CALCASOL under aerobic static conditions using the Zahn-Wellens / EMPA Test.

In this method, activated sludge, mineral nutrients and the test material as the sole carbon source are incubated together in a glass vessel placed on an orbital shaker under controlled conditions. The degradation of the test material is monitored by the determination of the dissolved organic carbon (DOC) at regular time intervals. The ratio of eliminated DOC after each interval to the value 3 hours after the start of the test is expressed as percentage biodegradation. The percentage biodegradation was plotted against time to give the biodegradation curve.

The produced CO₂ was determined during the test as an additional measure of the biodegradation expressed as the percentage of the theoretical value (% ThCO₂).

4 Materials and methods

4.1 Test system and test conditions

Inoculum	Activated sludge from the aeration tank of the ARA Werdhölzli (CH-8048 Zürich), a municipal biological waste water treatment plant, not adapted, not pre-conditioned; 0.2 g/l dry matter in the final mixture
Sampling	8 August 2011; 3 p.m.
Test units	1 litre closed glass bottle containing a total volume of test solution of 800 ml; aerated with CO ₂ -free air and fitted to gas-absorption bottles containing 125 ml of 0.13 M KOH
Incubation	Temperature-controlled dark room
Temperature	22 ± 2 °C
Test medium	Aerobic mineral salts medium (Table 1) prepared with de-ionized water (conductivity: <1.5 µS/cm; DOC: <0.3 mg/l)
Feed	None, CALCASOL and procedure control as sole organic carbon sources
Test duration	28 days

4.2 Test substance

Identification	CALCASOL
BMG sample no.	M1107-05614-01
Purity	treated as 100% pure
Test substance storage	At room temperature, protected from light
Stability	Stable under storage conditions

4.3 Reference substance

Identification	Diethylene glycol
Purity	99% pure
Source	VWR International, 201, rue Carnot, FR-94126 Fontenay sous Bois
Batch no.	S4920931 746
Reference substance storage	At room temperature protected from light
Stability	Stable under storage conditions

4.4 Test concentrations

Test substance	796 mg/l (50.8 mg C/l).
Reference substance	50.2 mg/l (as C)

4.5 Test procedure

The activated sludge was used after sampling from the treatment plant without adaptation. However, the sludge was pre-conditioned for 1-4 days (aerated but not fed). Prior to the test the sludge was washed twice with tap water and once with mineral medium. The activated sludge was applied to give a dry substance content of 0.2 g/l. The dry substance content of the activated sludge is gravimetrically determined in regular intervals after drying of the sludge at 105°C.

For each test series the following number of test flasks was set up:

Test suspension (T) 2 replicates:	containing activated sludge + test medium + test substance
Inoculum blank (B), 2 replicates:	containing activated sludge + test medium
Procedure control (R), 2 replicates:	containing activated sludge + test medium + diethylene glycol as ready biodegradable reference compound

The test vessels were stirred and aerated with synthetic CO₂-free air for a maximum test period of 28 days. The air leaving the individual vessels was passed through gas-absorption bottles filled with KOH. The pH-value was checked at the beginning and was adjusted to pH 7.4 +/- 0.2 with H₂SO₄. At the end of the test the pH was recorded.

The elimination of the test material was followed by DOC determinations at regular intervals. First samples were analyzed before the addition of the sludge and 3 h after starting the test. The trapped CO₂ in the gas-absorption bottles was determined as inorganic carbon (IC).

4.6 Chemical analyses

Dissolved organic carbon (DOC) was determined in duplicate with a Shimadzu 5000A, a Shimadzu 5050A TOC-Analyzer (Shimadzu Schweiz GmbH, Römerstr. 3, CH-4153 Reinach), or an Analytik Jena multi N/C 3100 TOC-Analyzer (Analytik Jena AG, DE-07745 Jena). For each determination at least 3 single injections were performed.

Aliquots from the individual test vessels were centrifuged (15 min at 4500 g) and the supernatant acidified to pH <2. Prior to analysis the samples were sparged with CO₂-free high purity air for 5 min to remove inorganic carbon.

Inorganic carbon (IC) was determined in samples taken from the gas-absorption bottles. The analysis was performed using the IC mode of the TOC-Analyzer. For each determination at least 3 single injections were performed.

Table 1 Composition of the mineral salt medium

Stock solution A (pH 7.4)	10 ml/l	Ammonium chloride (NH ₄ Cl)	0.50 g/l
		Di-sodium hydrogenphosphate (Na ₂ HPO ₄ x 2 H ₂ O)	33.40 g/l
		Potassium dihydrogenphosphate (KH ₂ PO ₄)	8.50 g/l
		Di-potassium monohydrogenphosphate (K ₂ HPO ₄)	21.75 g/l
Stock solution B	1 ml/l	Calcium chloride (CaCl ₂)	27.50 g/l
Stock solution C	1 ml/l	Magnesium sulfate (MgSO ₄ x 7 H ₂ O)	22.50 g/l
Stock solution D	1 ml/l	Iron (III) chloride (FeCl ₃ x 6 H ₂ O)	0.25 g/l

5 Evaluation of the test results

5.1 Definitions

The degree of biodegradation/elimination attained at the end of the test after 28 days or, if degradation is attained in less than 28 days, at an earlier time, is reported as "inherent, ultimate biodegradability in the static test (after x days)" if more than 70% biodegradation was reached. Evidence of "inherent, primary biodegradability" is given, if an elimination of the test substance between 20 and 70% was reached. According to the revised introduction of the guidelines for the testing of chemicals (OECD) the evaluation is made based on biological/chemical oxygen demand or DOC removal.

While the evaluation based on BOD/COD as well as based on IC gives information on the mineralization of the test substance, DOC removal yields only information on the elimination of the test substance. Hence, the evaluation whether the substance shows "inherent, ultimate biodegradability" or "inherent, primary biodegradability" was made based on the IC data.

Hence, also the degree of biodegradation was calculated as % of ThCO₂. The ThCO₂ (Theoretical carbon dioxide evolution in mg) is the total quantity of carbon dioxide calculated to be produced from the known or measured carbon content of the test material when fully mineralized.

If the result of analysis of the sample 3 h after the start of the test is significantly different from the initial value, the amount of deficient DOC is reported as "elimination due to adsorption by the activated sludge or other physico-chemical processes".

5.2 Calculation of the percentage biodegradation

The percentage removal of DOC is calculated using the following equation:

$$D_T = \left[1 - \frac{C_t - C_B}{C_A - C_{BA}} \right] \times 100$$

D_T is the biodegradation/elimination at time t in %

C_t is the mean DOC value of the test suspension at time t in mg/l

C_B is the mean DOC value of the blanks at time t in mg/l

C_A is the mean DOC value of the test suspension after 3 h in mg/l

C_{BA} is the mean DOC value of the blanks after 3 h in mg/l

The percentage biodegradation/elimination rounded to the nearest full percent is calculated from the DOC values of the last measurement.

The percentage biodegradation from the produced CO_2 is calculated from:

$$\% \text{ThCO}_2 = \frac{\text{mg IC from test unit} - \text{mg IC from inoculum blank}}{\text{mg DOC added as test material}} \times 100$$

$\% \text{ThCO}_2$ is the biodegradation at time t in % of the theoretical CO_2

IC is the mean inorganic carbon value of the individual absorption bottles at time t in mg/l

DOC is the organic carbon content of the added test material at the beginning of the test

5.3 Validity criteria

The test is considered valid if the procedure control shows the removal of the reference compound by at least 70% within 14 days.

6 Data compilation

The following data were recorded on data sheets and transcribed for compilation and analysis: amount of test and reference material applied, pH determinations.

The following data were recorded on-line (or on data sheets, as appropriate): DOC and IC determinations.

The TOC Analyzer has been validated with respect to data collection, storage and retrievability.

No statistical analysis was performed.

7 Results and discussion

7.1 Determination of biodegradation / elimination

The results of the DOC elimination are presented in Table 2 and Figure 1.

The mineralization data are summarised in Table 3.

Based on the data of the individual DOC determinations CALCASOL reached a biodegradation of 99% after 28 days.

The main degradation process occurred during the first 7 days, when more than 95% of the initial DOC was removed. Maximum biodegradation was attained after 10 days of incubation. No significant adaptation period (lag phase) was observed.

Significant elimination (27%) of the test substance due to adsorption to the activated sludge, on the glass surface or other physico-chemical processes was found as determined by means of DOC measurements 3 h after the start of the test.

The positive control, diethylene glycol, showed 99% biodegradation after 14 days of incubation thus confirming suitability of inoculum and test conditions. The test was considered valid, since the degradation of the reference compound reached more than 70% within 14 days of incubation.

The biodegradation of CALCASOL based on CO₂ evolution and calculated as % ThCO₂ reached 95% after 28 days of incubation, showing that the main part of the organic carbon of the test material was transformed into CO₂. The extent of mineralization of the procedure control with diethylene glycol was within the same range showing a value of 90% based on ThCO₂.

Based on these results CALCASOL can be termed as ultimately biodegradable under the conditions of the OECD guideline no. 302, since more than 70% degradation was attained after 28 days of contact time.

7.2 Remarks and alterations of the standard procedure

None.

7.3 Validity of the test

All the validity criteria as specified in section 5.3 were met.

Table 2 DOC concentrations of test suspension, inoculum blank and procedure control and calculation of degradation data.

Time (days)	Inoculum blank (B) *	Procedure control with diethylene glycol (R) *			Test suspension with test material (T) *		
	DOC (mg/l)	DOC (mg/l)	DOC net. (mg/l)	Degradation (%)	DOC (mg/l)	DOC net. (mg/l)	Degradation (%)
0	0.5	46.3	45.8	-	50.8	50.3	-
0.125	1.4	48.0	46.6	0	38.0	36.6	0
1	1.4	48.7	47.3	-2	37.0	35.6	3
3	1.6	40.3	38.7	17	20.8	19.2	48
7	1.8	2.9	1.1	98	3.1	1.3	97
10	1.4	1.6	0.2	100	1.9	0.5	99
14	1.8	2.3	0.5	99	2.1	0.2	99
17	2.1	2.2	0.1	100	2.6	0.5	99
21	2.2	2.2	0.0	100	2.5	0.3	99
24	2.5	3.2	0.7	98	3.2	0.7	98
27	2.5	2.6	0.1	100	2.6	0.2	100
28	1.6	2.0	0.4	99	1.8	0.2	99

* Mean of two replicates

Figure 1 Degradation curve for CALCASOL.




Table 3 IC concentrations, calculated from the concentrations in the gas absorption bottles, of test suspension, inoculum blank and procedure control and corresponding degradation data.

Time (days)	Test suspension IC (mg/l)	Procedure control IC (mg/l)	Inoculum blank IC (mg/l)	Biodegradation Test suspension (% ThCO ₂)	Biodegradation Procedure control (% ThCO ₂)
0	nd	nd	nd	-	-
7	34.9	47.8	13.1	43	69
14	67.1	64.8	24.2	84	81
21	71.5	69.3	28.5	85	81
28	82.0	79.0	33.8	95	90

nd not determined